(22) International Filing Date:

(30) Priority Data: 9806714.3

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



#### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: WO 99/50378 (11) International Publication Number: C11D 3/00, 3/20, 1/645, 1/835 A1 (43) International Publication Date: 7 October 1999 (07.10.99)

(74) Agent: MOLE, Peter, Geoffrey; Unilever plc, Patent Dept., PCT/EP99/01563 (21) International Application Number: Colworth House, Shambrook, Bedford MK44 1LQ (GB). 8 March 1999 (08.03.99)

GB

(71) Applicant (for AU BB CA CY GB GD GH GM IE IL KE LC LK LS MN MW NZ SD SG SL SZ TT UG ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P

27 March 1998 (27.03.98)

4BQ (GB).

(71) Applicant (for all designated States except AU BB CA CY GB GD GH GM IE IL IN KE LC LK LS MN MW NZ SD SG SL SZ TT UG US ZW): UNILEVER N.V. [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).

(71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]: Hindustan Lever House, 165/166 Backbay Reclamation, Mumbai 400 020, Maharashtra (IN).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KORB, Shimei [GB/GB]; Unilever Research Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside L63 3JW (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE,

**Published** 

With international search report.

SN, TD, TG).

(54) Title: FABRIC SOFTENING COMPOSITION

(57) Abstract

A fabric softening composition comprising 1 to 8 % by weight of one or more quaternary ammonium fabric conditioning compounds, stabilising agent and fatty alcohol having low and high temperature stability.

### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

## FABRIC SOFTENING COMPOSITION

The present invention relates to Fabric Softening compositions, in particular the invention relates to aqueous dispersions of biodegradable fabric softening compositions comprising a water insoluble cationic fabric softening agent, a stabilising agent and a fatty alcohol suitable as a rinse-added fabric softener composition.

Rinse added fabric softener compositions are well known.

Typically such compositions contain a water insoluble quaternary ammonium fabric softening agent dispersed in water at a level of softening agent up to 8% by weight in which case the compositions are considered dilute, or at levels from 8% to 50% in which case the compositions are considered concentrates. In addition to softening, fabric softening compositions desirably have other benefits. One is the ability to confer soil release properties to fabrics, particularly those woven from polyester fibre. Other

One of the problems associated with fabric softening compositions is the physical instability of such compositions when stored.

25

5

This problem is particularly noticeable in storage of dilute compositions at variable temperatures. Such composition tend to become unstable after storage at variable temperatures over time. Consumers, however, have high

- 2 -

expectations of characteristics such as viscosity and pourability from fabric softening compositions, expecting a specific level of viscosity and ease of pour which makes the composition convenient as well as pleasurable to use.

Physical instability of dilute compositions manifests as a decrease in viscosity to a level which is unacceptable, particularly in view of the consumers high demands.

Furthermore, unacceptable levels of thickening/gelling and phase separation can also occur as a result of storage over time and particularly at highly variable temperatures.

In the past physical stability of rinse added fabric softener compositions has been improved by the addition of viscosity control agents or anti-gelling agents. In EP 280550 (Unilever) it has been proposed to improve the physical stability of dilute compositions comprising biodegradable, ester-linked quaternary ammonium compounds and fatty acid by the addition of nonionic surfactants.

20 Certain stabilising agents not only stabilise fabric softener composition comprising biodegradable quaternary ammonium compounds but are also environmentally friendly, in that they show acceptable biodegradability and are not substantially toxic in aquatic systems.

25

It is also known from EP 13780 (Procter & Gamble) to form concentrated aqueous liquid fabric softening compositions from a mixture of a water-insoluble, cationic material and a nonionic material selected from hydrocarbons, fatty acids,

- 3 -

fatty esters and fatty alcohols; the nonionic material acting to improve the viscosity characteristics of a product when the level of cationic material is above 8%.

- It is also known from GB 2039556 and EP 13780 that preferred compositions can also include low levels of electrolyte such as respectively sodium chloride or calcium chloride, to further control product viscosity.
- 10 EP 056 695 (Procter & Gamble) discloses compositions comprising 12.3-25% cationic fabric softener and ethoxylated amines. WO 92/15745 (Procter & Gamble) discloses compositions comprising 10-35% cationic fabric softener, a highly branched fatty alcohol and a fatty alcohol ethoxylate.

GB 2 170 829 and EP 394 133 (Colgate-Palmolive) disclose compositions comprising 3-8% and 2-35% respectively cationic fabric softener that do not need non ionic surfactant emulsions to keep viscosity and stability acceptable.

20

25

\_\_\_\_\_

GB 2 139 259 and EP 122 141 (Unilever) disclose compositions comprising 8% or more cationic fabric softener and non ionic materials with an HLB of less than 10, e.g. fatty alcohols.

EP 409 504 (Unilever) disclose compositions comprising cationic fabric softener and fatty alcohols as extenders for the softener.

- 4 -

GB 1 538 094 discloses compositions comprising cationic fabric softeners, fatty alcohols and non-ionic emulsifiers.

- Surprisingly, we have found that low and high temperature stability of dilute compositions containing biodegradable quaternary ammonium compounds may be improved by the addition of a mixture of selected stabilising agents and fatty alcohol.
- Thus, according to one aspect of the invention there is provided a fabric softening composition comprising:
  - a) from 1 to 8% by weight of one or more quaternary ammonium fabric conditioning compounds;
- 15 b) a stabilising agent selected from a nonionic surfactant or a single long chain alkyl cationic surfactant or mixtures thereof; and
  - c) a fatty alcohol
- Such compositions show improved high temperature stability, (in particular stability at 37°C), stability at ambient temperatures as well as stability at low temperatures. By high temperature stability is meant stability at temperatures above the ambient temperature to which the composition is normally exposed. Low temperature stability means stability at temperatures below the ambient temperature to which the composition is normally exposed.

- 5 -

According to another aspect of the invention there is provided a process, for making a liquid fabric softening composition of the invention, comprising the steps of;

- 5 (i) mixing and heating the quaternary ammonium compound, stabilising agent and fatty alcohol to form a melt and
  - (ii) dispersing the melt in water.
- According to another aspect of the invention there is provided the use of a composition according to the invention to form a stable aqueous fabric softening composition.
- According to another aspect of the invention there is

  provided the use, in a fabric softening composition

  comprising a water insoluble quaternary ammonium material,

  of a mixture of a stabilising agent and fatty alcohol, in

  order to improve the low, ambient and high temperature

  stability of the composition.

20

Preferably, the compositions of the invention are liquids comprising an aqueous base.

At least one of the one or more quaternary ammonium fabric conditioning compounds is in, one preferred embodiment, a quaternary ammonium compound having at least one ester linkage, especially a compound having two C<sub>8-20</sub> alkyl or alkenyl groups connected to the quaternary ammonium head group via at least one ester link. It is more preferred if

- 6 -

the quaternary ammonium compound has two ester links present. Preferably the fabric softening composition contains either one or more ester linked quaternary ammonium compounds, or, one or more non-ester linked quaternary ammonium compounds.

Preferably the quaternary ammonium fabric conditioning compounds for use in the compositions according to the invention are represented by the formula:

10

$$OOCR^{2}$$
 $(R^{1})_{3} N^{+} - (CH_{2})_{n} - CH X^{-}$ 
 $(I)$ 
 $CH_{2}OOCR^{2}$ 

15

20

wherein each  $R^1$  group is independently selected from  $C_{1-4}$  alkyl, alkenyl or hydroxyalkyl groups; each  $R^2$  group is independently selected from  $C_{8-28}$  alkyl or alkenyl groups;  $X^1$  is a compatible anion; and n is an integer from 0-5;

or by the formula:

$$R^{1}$$

$$R^{1} - N^{+} - (CH_{2})_{n} - T - R^{2} X^{-} \qquad (II)$$

$$(CH_{2})_{n} - T - R^{2}$$
wherein  $R^{1}$ ,  $X^{-}$ ,  $n$  and  $R^{2}$  are as defined above, and

- 7 -

The preferred compounds of type (I) and their method of preparation are, for example, described in US 4 137 180 (Lever Brothers). A particularly preferred compound of type (I) is 1,2 bis[hardened tallowoyloxy]-3-trimethylammonium propane. Preferably these compounds comprise small amounts of the corresponding monoester as described in US 4 137 180 for example 1-hardened tallowoxy 2-hydroxy-3-trimethylammonium propane chloride.

The preferred compounds of type (II) is di[2-(hardened tallowoyloxy)ethyl] dimethylammonium chloride.

Of the quaternary ammonium compounds not having an ester linkage suitable examples include di-(hardened tallow) dimethylammonium chloride and the compound sold under the Tradename 'Accosoft 460HC'.

The level of quaternary ammonium compound is from 1% to 8% by weight of the total composition, more preferably from 1.5% to 7.9%, most preferably from 2% and 7%, such as 3% to 5%.

25

30

In a preferred embodiment of the invention, the ratio of stabilising agent to fatty alcohol is greater than or equal to 1:1. This range provides improved physical stability of the composition. The weight ratio of stabilising agent to

- 8 -

fatty alcohol is preferably is greater than or equal to 1:1.5, more preferably greater than or equal to 1:1.8. Higher ratios of greater than or equal to 1:3 or 1:7 are also effective. Depending upon the required viscosity of the product ratios of greater than or equal to 1:10 may be used. By adjusting the ratio above 1:1 the desired viscosity of the product is obtained. Typically the higher the proportion of fatty alcohol used the higher is the resultant viscosity of the product.

10

15

20

25

Compositions comprising from 1 to 8% level of quaternary ammonium compound are considered dilute fabric softening compositions. These pose a different problem in managing product viscosity via stability of the composition than the problem posed by concentrated fabric softening compositions.

Compositions according to the invention contain a stabilising agent selected from a nonionic surfactant or a single long chain alkyl cationic surfactant or mixtures thereof.

Suitable nonionic surfactant stabilisers which can be used include the condensation products of  $C_8$ - $C_{30}$  primary or secondary, linear or branched alcohols alkoxylated with 10 or more moles of alkylene oxide, preferably 10 to 20 moles of alkylene oxide, more preferably between 15 and 20 moles of alkylene oxide. Preferably the condensation product is of a  $C_{10}$ - $C_{22}$  primary or secondary, linear or branched alcohol.

- 9 -

Preferably the alkylene oxide is ethylene oxide. The alcohols may be saturated or unsaturated. Particularly preferred are Genapol T-110, Genapol T-150, Genapol T-200, Genapol C-200, Genapol 0-100 and Genapol 0-150 all ex Hoechst AG, Lutensol AT18 ex BASF. Preferably the nonionic stabiliser has an HLB of between 10 and 20, more preferably 12 and 20.

Preferably, the level of nonionic surfactant stabiliser is
within the range of from 0.01 to 10% by weight, more
preferably from 0.05 to 5% by weight most preferably from
0.1 to 3% by weight, such as 0.15 to 1.5% by weight.
Frequently amounts of 0.01 to 1% by weight, such as 0.01 to
0.5% of nonionic surfactant stabiliser may be used.

15

Further possible stabilisers suitable in the present invention are mono (single) long chain alkyl cationic surfactants. Preferably, quaternary ammonium salts of the general formula:

20

$$[R^2 - N^{\oplus} - R_3] X$$

wherein the  $R^2$  group is  $C_{10}$ - $C_{22}$  hydrocarbon group, preferably  $C_{12}$ - $C_{18}$  alkyl group or the corresponding ester linkage interrupted group with a short alkylene ( $C_1$ - $C_4$ ) group between the ester linkage and the N, and having a similar

- 10 -

hydrocarbon group, e.g., a fatty acid ester of choline, preferably  $C_{12}$ - $C_{14}$  (coco) choline ester and/or  $C_{16}$ - $C_{18}$  tallow choline ester are used. Each R is a  $C_1$ - $C_4$  alkyl or substituted (e.g. hydroxy) alkyl, or hydrogen, preferably methyl, and the counterion X is a compatible anion, for example, chloride, bromide, methyl sulphate etc. Such surfactants can protect the quaternary ammonium conditioning compound from interacting with anionic surfactants and/or detergent builders that are carried over into the rinse.

10

The stabilising agent may be a mixture selected from different nonionic surfactants and/or single long chain alkyl cationic surfactants.

The compositions of the invention also contain a fatty alcohol.

Suitable fatty alcohols which can be used in the present invention include fatty alcohols of about 10 to 40 carbon atoms. More preferably the fatty alcohol may have a straight or branched chain alkyl or alkenyl group having from about 10 to 24, preferably from about 10 to 20, especially from about 12 to 20 carbon atoms. Specific examples of the fatty alcohol include decanol, dodecanol, tetradecanol, pentadecanol, hexadecanol, octadecanol, and mixtures thereof.

- 11 -

Furthermore, the fatty alcohol may be of a natural or synthetic origin and may include, for example, mixed alcohol, such as C<sub>16</sub> to C<sub>18</sub> alcohols prepared by Ziegler polymerisation of ethylene or by reduction of fatty acids.

5 The fatty alcohol is preferably present in the composition at a ratio equal to or greater than 1:1 relative to the stabilising agent. Preferably, it is present in an amount of 0.1 to 20% by weight of the composition, most preferably 0.3% to 12%, more preferably 0.5% to 10%, such as 0.5% to 10%. Frequently the compositions of the invention may comprise of 0.1 to 2% by weight, such as 0.1 to 1% of the fatty alcohol.

We have found that particularly good compositions of the invention comprise 1 to 8% by weight of the quaternary ammonium compound, from 0.01 to 5% by weight of the nonionic stabilising material and between 0.2 to 20% by weight of the fatty alcohol.

15

The composition can also contain one or more optional ingredients, selected from non-aqueous solvents, pH buffering agents, perfumes, perfume carriers, fluorescers colourants, hydrotopes, antifoaming agents, antiredeposition agents, enzymes, optical brightening agents, opacifiers, anti-shrinking agents, anti-wrinkle agents, anti-spotting agents, germicides, fungicides, anti-oxidants, anti-corrosion agents, drape imparting agents, anti-static agents and ironing aids.

- 12 -

The composition may also contain nonionic fabric softening agents such as lanolin and derivatives thereof.

The compositions of the invention may be prepared by a

5 method where the cationic fabric softening agent,
stabilising agent and fatty alcohol are premixed and heated
together to form a clear melt. The molten mixture thus
formed is added to water at a suitable temperature to keep
the aforementioned components molten, e.g. 70°C to 80°C,

10 over a period of at least one minute, with constant stirring
to form a dispersion.

The compositions of the invention may be used to form stable aqueous fabric softening compositions. Also according to the invention in fabric softening compositions comprising 1 to 8% by weight of one or more quaternary ammonium fabric conditioning compounds, a mixture of stabilising agent and fatty alcohol in a weight ratio of greater than or equal to 1:1 is used to improve the stability of the composition at low, ambient and high temperatures.

15

20

Preferably, according to these aspects of the method of preparing the compositions and their uses, the cationic fabric softening agent is represented by one of the two formulae set out above. Other preferred features of the use, in particular with respect to the non-ionic stabiliser and fatty alcohol, correspond to those for the first aspect of the invention.

The invention will now be illustrated by the following nonlimiting examples. In the examples all percentages are expressed by weight.

## 5 <u>Examples</u>

Liquid fabric softening compositions were made as follows.

The cationic fabric softening agent, stabilising agent and fatty alcohol were premixed and heated together to form a clear melt. The molten mixture thus formed was added to water at 70°C to 80°C over a period of at least one minute, with constant stirring to form a dispersion.

Composition	A	B <sup>7</sup>	С	D	E <sup>7</sup>	F	G	
DEEDMAC <sup>1</sup>	_ 4.8	4.8 -	4.6	4.4	4.8	4.6	4.4	
Genapol C200 <sup>2</sup>	0.1	0.1	0.1	0.1	0.2	0.2	0.2	
Laurex CS <sup>3</sup>	0.75		0.36	0.72		0.36	0.72	
Perfume <sup>4</sup>	0.32							
Natrasol plus 331 <sup>5</sup>	.005							
Water and minors	up to 100%							

## 15 NOTES

- 1. DEEDMAC is a Di[2-(hardened tallowoyloxy)ethyl] dimethylammonium chloride.
- 20 2. Coco alcohol ethoxylated with 20 moles of ethylene oxide ex Hoechst AG.
  - Tallow alcohol ex Albright & Wilson.

- 14 -

- 4. Softline DM53 ex Givaudan-Rouve
- 5. Thickener/polymer.
- 5 6. Minors associated with the raw materials present in all components of the examples.
  - 7. Examples B and E are comparative as they do not contain any fatty alcohol.

The viscosity of the compositions A - G was measured by Haake rotoviscometer after 1, 4 and 6-8 weeks storage at ambient temperature or at 37°C. The results below were obtained.

15

Viscosity at 110s mPas	A	В	С	D	E	F	G
Initial	70	130	60	105	23	45	83
1 week at 37°	63	79	41	90	12	40	71
2	58	63	39	85	11	38	71
3	57	52	41	88	9	36	66
4	55	30	35	75	4	27	67
5	55	20	34	83	5	34	83
6	55	15	32	79	5	33	73
7		15	32	79	5	37	77
8	56	10	32	71	4	35	76
				:			
Initial	70						
1 week at ambient	61	130	60	105	23	45	83
2	56	110	43	87	21	35	67
3	58	110	44	85	21	38	63

- 15 -

4	54	106	45	90	20	38	70
5	56	102	44	81	12	33	72
6	53	102	44	81	12	33	72
7		98	47	89	10	38	63
8	56	87	44	75	7	32	63

By comparison with comparative examples B and E these results show that addition of a mixture of fatty alcohol and nonionic stabiliser to compositions comprising ester linked quaternary ammonium compounds counteracts destabilisation at ambient and high temperatures to give more stable compositions.

- 16 -

#### CLAIMS

15

25

1. A fabric softening composition comprising:

- 5 a) from 1 to 8% by weight of one or more quaternary ammonium fabric conditioning compounds;
  - b) a stabilising agent selected from a nonionic surfactant or a single long chain alkyl cationic surfactant or mixtures thereof; and
- 10 c) a fatty alcohol.
  - 2. A composition according to claim 1 wherein one or more of the one or more quaternary ammonium fabric conditioning compounds has at least one ester linkage.

3. A composition according to either claim 1 or claim 2 in which one or more of the quaternary ammonium fabric conditioning compounds is represented by the formula:

wherein each  $R^1$  group is independently selected from  $C_{1-4}$  alkyl, alkenyl or hydroxyalkyl groups; each  $R^2$  group is independently selected from  $C_{8-28}$  alkyl or alkenyl

- 17 -

groups;  $X^{-}$  is a compatible anion; and n is an integer from 0-5;

or by the formula:

5

10

20

$$R^{1}$$
 $R^{1} - N^{+} - (CH_{2})_{n} - T - R^{2} \quad X^{-}$ 
 $CH_{2})_{n} - T - R^{2}$ 

(II)

wherein  $R^1$ ,  $X^2$ , n and  $R^2$  are as defined above, and

- 4. A composition according to anyone of claims 1 to 3 wherein the quaternary ammonium compound is 1,2 bis[hardened tallowoyloxy]-3-trimethylammonium propane chloride or di[2-(hardened tallowoyloxy)ethyl] dimethylammonium chloride.
- 5. A composition according to claim 1 wherein the
  quaternary ammonium compound is di-(hardened tallow)
  dimethylammonium chloride.

- 6. A composition according to any preceding claim wherein the weight ratio of b:c is greater than or equal to 1:1.
- 5 7. A composition according to any preceding claim wherein the stabilising agent comprises a  $C_8$ - $C_{30}$  primary or secondary linear or branched alcohol alkyoxylated with 10 or more moles of alkylene oxide.
- 10 8. A composition according to any preceding claim wherein the fatty alcohol comprises a chain length of about 10 to 40 carbon atoms.
- 9. A composition as claimed in any preceding claim wherein the composition comprises 1 to 8% by weight of the quaternary ammonium compound, from 0.01 to 5% by weight of the nonionic stabilising material and between 0.2 to 20% by weight of the fatty alcohol.
- 20 10. A process for making a liquid fabric softening composition as claimed in any of claims 1 to 9 comprising the steps of
- (i) mixing and heating the quaternary ammonium

  compound, stabilising agent and fatty alcohol to
  form a melt and
  - (ii) dispersing the melt in water.

- 11. Use of a composition as defined in any of claims 1-9 to form a stable aqueous fabric softening composition.
- 12. Use, in a fabric softening composition comprising 1-8% by weight of one or more water insoluble quaternary ammonium compounds, of a mixture of a stabilising agent and fatty alcohol, in order to improve the low, ambient and high temperature stability of the composition.
- 10 13. Use, according to either of claims 11 or 12 wherein the ratio of stabilising agent and fatty alcohol is greater than or equal to 1:1.
- 14. Use, according to either claim 12 or 13, wherein the stabilising agent is the condensation product of  $C_8$ - $C_{30}$  primary or secondary linear or branched alcohols alkoxylated with 10 or more moles of alkylene oxide and wherein the fatty alcohol has between 10 and 40 carbon atoms.

20

15. Use according to any of claims 11-14 wherein the quaternary ammonium compound is represented by the formula:

$$OOCR^{2}$$
25
$$(R^{1})_{3} N^{+} - (CH_{2})_{n} - CH X^{-} (I)$$

$$CH_{2}OOCR^{2}$$

- 20 -

wherein each  $R^1$  group is independently selected from  $C_{1-4}$  alkyl, alkenyl or hydroxyalkyl groups; each  $R^2$  group is independently selected from  $C_{8-28}$  alkyl or alkenyl groups;  $X^2$  is a compatible anion; and n is an integer from 0-5;

or by the formula:

5

wherein  $R^1$ , n,  $X^-$ , and  $R^2$  are as defined above, and

Inte Ional Application No PCT/EP 99/01563

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 C11D3/00 C11E C11D3/20 C11D1/835 C11D1/645 According to International Patent Classification (IPC) or to both national classification and IPC **B. FIELDS SEARCHED** Minimum documentation searched (classification system followed by classification symbols) IPC 6 C11D Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the International search (name of data base and, where practical, search terms used) C. DOCUMENTS CONSIDERED TO BE RELEVANT Relevant to claim No. Citation of document, with indication, where appropriate, of the relevant passages Category \* 1-3,7-9X WO 94 04643 A (COLGATE PALMOLIVE CO) 3 March 1994 see claims 1-4,8; example 1B X GB 2 170 829 A (COLGATE PALMOLIVE CO) 1,8,9,11 13 August 1986 cited in the application see claims 1,5-11; example 12 see page 2, line 35 - line 38 see page 4, line 35 - line 40 see page 7, 1 ine 34 - 1 ine 41 χ FR 2 257 728 A (PROCTER & GAMBLE) 1,6-11 8 August 1975 see claims 1-6,10; example 3 Further documents are listed in the continuation of box C. Patent family members are listed in annex. Special categories of cited documents: "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the "A" document defining the general state of the art which is not considered to be of particular relevance Invention "E" earlier document but published on or after the international "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed Invention cannot be considered to involve an inventive step when the document is combined with one or more other such docu-"O" document referring to an oral disclosure, use, exhibition or ments, such combination being obvious to a person skilled in the art. other means document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family Date of the actual completion of the international search Date of mailing of the international search report 28 June 1999 21/07/1999 Name and mailing address of the ISA Authorized officer European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016 Loiselet-Taisne, S

2

Intra Bonal Application No PCT/EP 99/01563

C (Cartley	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	101/21 33/01003
Category °		Relevant to claim No.
		1.15
Α	EP 0 409 504 A (UNILEVER PLC; UNILEVER NV (NL)) 23 January 1991 cited in the application see page 4, line 7 - line 10 see page 6, line 5 - line 10 see claims 1-3,6,8; example 3C	1-15
X	see page 6, line 5 - line 10 see claims 1-3,6,8; example 3C  GB 1 538 094 A (HOECHST AG) 10 January 1979 cited in the application see claims; examples; table 1	1,6-9

Information on patent family members

Int: 1onal Application No PCT/EP 99/01563

Patent document cited in search report		Publication date		atent family member(s)	Publication date
WO 9404643	Α	03-03-1994	EP	0656935 A	14-06-1995
GB 2170829	A	13-08-1986	US AT AU AU BBRAHE BC CDE FF GBB GKK HKE INP PT SUS ZW	4772403 A 395614 B 19986 A 5256586 A 627877 B 5501490 A 904142 A 8600349 A 1331681 A 671581 A 3602089 A 38486 A 17690 A 860401 A 2576614 A 2207154 A,B 2207446 A,B 860252 A 693 A 2093 A 2193 A 57656 B 166653 A 61179372 A 86276 A 8600219 A 23694 A 81911 A,B 8600364 A 4844823 A 1086 A 1086 A	20-09-1988 25-02-1993 15-06-1992 07-08-1986 03-09-1992 30-08-1990 30-07-1986 14-10-1986 30-08-1994 15-09-1989 21-08-1986 31-07-1986 31-07-1986 01-08-1986 25-01-1989 01-02-1989 29-05-1986 15-01-1993 21-01-1993 21-01-1993 21-01-1993 30-06-1990 12-08-1986 04-08-1986 04-08-1986 04-08-1986 04-08-1986 04-08-1986 04-07-1989 01-02-1986 31-07-1986 04-07-1989 28-08-1987 02-09-1987
FR 2257728	A	08-08-1975	US BE CA DE GB JP NL	3974076 A 824294 A 1038110 A 2500111 A 1487432 A 50105997 A 7500297 A,B,	10-08-1976 10-07-1975 12-09-1978 17-07-1975 28-09-1977 21-08-1975 15-07-1975
EP 0409504	A	23-01-1991	AU CA DE DE ES JP JP	637803 B 5894790 A 2021010 A 69028667 D 69028667 T 2093016 T 2611035 B 3090677 A	10-06-1993 17-01-1991 18-01-1991 31-10-1996 06-03-1997 16-12-1996 21-05-1997 16-04-1991
GB 1538094	A	10-01-1979	DE AT AT BE DK FR	2503026 A 345417 B 44276 A 837902 A 27576 A 2298600 A	29-07-1976 11-09-1978 15-01-1978 26-07-1976 26-07-1976 20-08-1976

information on patent family members

int tional Application No PCT/EP 99/01563

				99/01563	
Patent document cited in search report	Publication date	P	atent family member(s)	Publication date	
GB 1538094 A		LU NL	74239 A 7600535 A	31-12-1976 27-07-1976	
			•		
			•		